

FOODMAX AW 22

Product code: 264000201

Range of multipurpose lubricating oils for the food industry

This product is formulated using specially selected highly refined base stocks in combination with the latest additive technology. The product is nontoxic and suitable for use in applications where incidental contact with food or raw materials during the production is possible or likely. Thanks to its great performance characteristics and carefully chosen additives, the oils can be used in most applications in the manufacturing process in the food production and processing industry.

The product is available in a wide range and is NSF, Kosher and Halal approved.

Applications

General lubrication

The product can be used for all kinds of general lubrication. For example, for bearings, slides, chains, and small mechanisms, which need a medium pressure oil that provides a clean and non-contaminating lubrication. The application is easily done either automatic or by dropping, spraying or manually.

Air tool lubrication

This product is perfectly suitable for airline and air tool lubrication. It will protect the pipes from corrosion as well as all the elements and valves of the pneumatic network. The use of this product will provide a trouble-free operation. The de-emulsifying characteristics of this product provide easy draining of the moisture that is present in compressed air. It is recommended for air lubrication whenever there is a chance that the air will be in contact with food, for example in case of spraying of food additives.

Hydraulic oil

Thanks to its excellent anti wear properties the AW range is used as hydraulic fluid for both power and motion transfer in machinery operated close to food production processes:

- High viscosity index, high temperature behavior is excellent. This product shows rather flat viscosity-temperature curves, which results in a smooth operation in both high and low temperature lubrication
- Low pour point which allows operation at temperatures below $< 0^{\circ}\text{C}$ and increased performance in start-up operations
- High shear stability
- Outstanding anti foam properties
- Excellent demulsifying capacity

Conveyor lubrication

In the beverage industry very often a mixture of soap and water is used to lubricate stainless steel conveyors in combination with glass bottles. The soap mixture will give a messy workplace and will stain labels. It has proven to do an excellent job here. Usually, a very small amount is sprayed on the conveyor (almost dry lubrication).

This product has been approved by DROPSA, beverage equipment supplier for use on the conveyors.



FOODMAX AW 22

Product code: 264000201

Dielectric oil

Its fluids possess excellent isolating and dielectric properties. It is amongst others being used as dielectric oil in underwater pumps that are used in drinking water.

Anticorrosive agent

It can be used as light anticorrosive protector of metal surfaces which might be in contact with food products. Examples are wires for canned meat sealing, conveyor or slides in manufacturing equipment and handling food packaging. It can also be used to clean and polish stainless steel.

Typical Performance Data



Typical	Test Method	Value
Density @ 20 °C, g/ml	ASTM D4052	0.848
Viscosity @ 40 °C, cSt	ASTM D445	22
Viscosity Index	ASTM D2270	105
Pour point, °C	ASTM D97	-22
Flash point, °C	ASTM D92	180
Acidity index, mg KOH/gr		0.8
Aniline point, °C		105
Copper corrosion, 3h/100 °C	ASTM D130	1a
Steel corrosion, distilled water		Pass
De-emulsifying index		40/37/3 (30')
NSF approval		138240
Kosher		Yes
Halal		Yes

All performance data on this Technical Data Sheet are indicative only and can vary during production.